Model/s:			SRS 20					
Condensing Boiler/s:			Yes					
Low Temperature (**) Boiler/s: B11 Boiler/s: Cogeneration Space Heater: Combination Heater:			No					
			No					
			No	Equipped with a supplementary heating system:			No	
			Yes					
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit	
Nominal heat output	D	20	kW	Seasonal space heating energy efficiency	ης	93,408	%	
	P _{rated}			Energy efficiency class		Α		
For boiler space heaters and boiler combination heaters: Useful heat output				For boiler space heaters and boiler combination heaters: Useful efficiency				
At nominal heat output and high- temperature regime (*)	P ₄	19,420	kW	At nominal heat output and high-temperature regime (*)	η_4	87,435	%	
At 30% of nominal heat output and low-temperature regime (**)	P ₁	1,961	kW	At 30% of nominal heat output and low- temperature regime (**)	η ₁	98,086	%	
Auxiliary electricity consumption	•		•	Other items			•	
At full load	el _{max}	0,073	kW	Standby heat losses	P _{stby}	0,063	kW	
At part load	el _{min}	0,033	kW	Ignition burner energy consumption	P _{ign}	2,133	kW	
In standby mode	P _{SB}	0,003	kW	Sound power level, indoors	L _{WA}	39	dB	
For boiler combination heaters:								
Declared load profile:		V	1	Domestic hot water production efficiency	n	85,004	- %	
	XL			Energy efficiency class	η _{wн}	Α	70	
Daily electrical power consumption	Q _{elec}	0,185	kWh	Daily gas consumption	Q _{fuel}	22,838	kWh	
Annual electricity consumption	AEC	40,748	kWh	Annual fuel consumption	AFC	18,088	GJ	
Contact information	ALARKO CARRIER SAN. TİC. A.Ş., GOSB - Gebze O.S.B., Şahabettin Bilgisu Cad., 41400, Gebze/Kocaeli/Turkey							

^(*) High temperature regime means 60 °C on return and 80 °C on flow.

^(**) Low temperature regime means 30 °C for condensing boilers, 37 °C for low-temperature boilers and 50 °C for for other appliances on return temperature.